

6000 Series

Commercial Grade Forage Boxes
Front Unload • Front & Rear Unload

Meyer



**STRENGTH - SPEED
SIZE - PRODUCTIVITY**

*The 6000 Series
Has It All!*

Bullet Proof, All Steel Frame
Massive, High Performance Gear Boxes
High Impact, **Solid Poly** Floor
High Capacity 7' Sides With 4th Beater
Fastest Unload Time in the Industry

**MEETING THE DEMANDS OF TODAY'S
HIGH CAPACITY USER WITH EFFICIENCY,
STRENGTH AND SIZE
AVAILABLE IN: 20' — 22' — 24' LENGTHS**



Torsion-Style, Spring-Loaded *Apron
Tighteners* Protect Your Floor Chains

MEMBER



Farm Equipment Buyers Trust The Name Meyer!



Dimensions • Specifications • Options



STANDARD VARIABLE DRIVE

Commercial-Grade Gearboxes Dwarf the Competition!
 Large Drive Couplers for Switching Front to Rear. (6200)
 New TSS Speed Ratio Provides more Efficient Performance for Larger Loads.
 Less Moving Parts, Spring Loaded Roller Chain Tightening.



CAB CONTROLLED HYDRAULIC DRIVE SAFE – SIMPLE – CONVENIENT AND PRODUCTIVE!

Operate all front and rear unload functions from the seat of your truck or tractor. No Belts and less moving parts than a traditional variable speed system! Includes hyd. conveyor lift.

Perfect for truck and trailer mount applications.
 Requires 25 gpm flow



REAR GATE DELAY

Faster Unloading and More Positive Door Latching (Standard Equipment on 6200)

OPTIONAL GRAIN KIT

Available with False Front Panel (for 6200 only)

Dimensions	Front Unload	6620	6622	6624
	Front & Rear Unload	6220	6222	6224
Floor Length		20'6"	22'6"	24'6"
Overall Length (6200)		24'5"	26'5"	28'5"
Inside Height (w/o roof)		7'	7'	7'
Overall Height (w/o roof)				
top of side		105"	105"	105"
top of door pivot (+3" gds) (6200 only)		114"	114"	114"
<i>*Less 4" truck & trailer mounts</i>				
Overall Height (w/roof)		126"	126"	126"
Inside Width		87"	87"	87"
Overall Width w/conveyor extension up		109.5"	109.5"	109.5"
Stringer Width/Height				
truck/trailer mount		33.5"/6"	33.5"/6"	33.5"/6"
wagon mount		42"/10"	42"/10"	42"/10"
Weight (less options) (6200)		7,465#	7,840#	8,235#
Capacity (struck level) cu. ft. w/o roof		1040	1142	1243

Specifications

Front Apron Drive Shaft	2"	2"	2"
Rear Drive Roller (6200)	2 1/2" Hvy Tubing	2 1/2" Hvy Tubing	2 1/2" Hvy Tubing
Upright Spacing	16"	16"	16"
Floor Supports (all steel - 16" centers)	2x2 tubing	2x2 tubing	2x2 tubing
Double - 3" Angle Top Rail (no side supports needed)	Standard	Standard	Standard
Commercial Grade Gearbox/Drive Coupler	Standard	Standard	Standard

Standard Features

TSS - Total Speed System - Variable Speed	Standard	Standard	Standard
Low Range 0-7.5'/minute			
High Range 0-17'/minute			
Apron Chains (heavy duty pintle)	667X	667X	667X
Spring Loaded/Torsion Style Apron Tightener	Standard	Standard	Standard
Auger Feathering System & Conveyor Clutch	Standard	Standard	Standard
Cross Conveyor Chain Hold-Downs	Standard	Standard	Standard
Superslide, Solid Poly Floor (no plywood)	Standard	Standard	Standard
All Steel Frame - 16" centers (no wood)	Standard	Standard	Standard
7' Sides w/4th Beater System	Standard	Standard	Standard
Fold-Down Conveyor Extension w/lift assist	Standard	Standard	Standard
Rear Gate Delay System (6200)	Standard	Standard	Standard

Optional Equipment

Hydraulic Front Drive System	Optional	Optional	Optional
Hydraulic In-Cab Controls (6600 or 6200)	Optional	Optional	Optional
Roof Assembly(removable)/Hood Assembly(right hand only)	Optional	Optional	Optional
Rear Grain Kit (6200 only)	Optional	Optional	Optional
False Front Gate for Grain Kit	Optional	Optional	Optional
Truck Mnt./Trailer Mnt./Wagon Mnt.	Optional	Optional	Optional
TARP SYSTEMS (w/front enclosures)			
Front to Back Scissor Tarp (electric)	Optional	Optional	Optional
Side to Side Roll Tarp (electric)	Optional	Optional	Optional
Clad Tuff Fiberglass Sides & Back	Optional	Optional	Optional
Barn Door Rear Gate with Closure	Optional	Optional	Optional

XT2200 TANDEM TRAILER



For close hauls, muddy conditions, balanced load.

DIMENSIONS & SPECIFICATIONS

Spindle Size	3/2"
Hub Size	10 Bolt 15,000#
Capacity	22 Ton
Weight	3810#
Bed Height	44"
Overall Width	102.5"
Specify Box Length	18 - 20 - 22 - 24'
Construction	Tubular Steel

XTS/XTSS models available with suspension/steering

American Made – American Owned

YOUR DEALER IS:

Meyer Mfg. Corp.

Dorchester, Wisconsin 54425

Phone: 715/654-5132

FAX: 715/654-5513 • 1-800-325-9103

email: sales@meyermfg.com

home page: www.meyermfg.com

Also Available:

3200/4200 Front/Rear Unloads 16-22' • "Boss" 8100 Rear Unloads 18-26' • "Boss" 9100 Rear Unloads 26-40'

Over
65 years
 of service
 to our customers